

Fox ESS ECS BATTERY STORAGE SYSTEM



HIGH VOLTAGE BATTERY FROM Fox ESS

The ECS is a high-performance, scalable battery storage system. The modular design allows for maximum flexibility, making it suitable for a broad range of storage applications.

Additional batteries can be installed in series, allowing for a maximum storage capacity of 20.16kWh. Installation is easy, with a plug and play solution that can save valuable time for installers.

- 2.88kWh capacity
- Scalable to 20.16 kWh
- 90% Depth of Discharge
- Large temperature tolerance
- Easy installation
- CAN/RS485 communication
- High voltage



High Voltage



Simple Installation



Height Efficiency



Expandable System



90% DoD

Fox ESS

ECS SERIES

ECS2900-H2/H3/H4/H5/H6/H7

| Model | ECS2900 -H2 | ECS2900 -H3 | ECS2900 -H4 | ECS2900 -H5 | ECS2900 -H6 | ECS2900 -H7 |
|--|---------------------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| ELECTRICAL CHARACTERISTICS | | | | | | |
| Battery Type | LiFePO4 Prismatic Cell | | | | | |
| Battery Module | 1*CM2900 1*CS2900 | 1*CM2900 2*CS2900 | 1*CM2900 3*CS2900 | 1*CM2900 4*CS2900 | 1*CM2900 5*CS2900 | 1*CM2900 6*CS2900 |
| Nominal Capacity[Wh] | 5760 | 8640 | 11520 | 14400 | 17280 | 20160 |
| Nominal Voltage [V] | 115.2 | 172.8 | 230.4 | 288 | 345.6 | 403.2 |
| Operating Voltage[V] | 97.2 ~ 131.4 | 145.8 ~ 197.1 | 194.4 ~ 262.8 | 243 ~ 328.5 | 291.6 ~ 394.2 | 340.2 ~ 459.9 |
| Recommend Discharge Current [A] | 25 | | | | | |
| Max.Charge/Discharge Current [A] | 50 | | | | | |
| Peak Discharge Current [A] | 65 @30sec | | | | | |
| Battery Pack Round-Trip Efficiency [%] | >95 | | | | | |
| Depth of discharge [%] | 90 | | | | | |
| Cycle Life* ¹ | ≥6000 | | | | | |
| Communication | CAN, RS485 | | | | | |
| Display | CS: LED*1, CM: LED*6 | | | | | |
| Scalability | Max. 7 Modules in Series | | | | | |
| OPERATING CONDITIONS | | | | | | |
| Installation Location | Outdoor/ Indoor (Stand) | | | | | |
| Operating Temperature [°C]* ² | Charge: 0 ~ 55 Discharge: -10 ~ 55 | | | | | |
| Storage Temperature [°C] | -20 ~ 55 | | | | | |
| Cooling method | Natural Convection | | | | | |
| Humidity [%] | 5 ~ 95 (No Condensing) | | | | | |
| Altitude [m] | Max. 2,000 | | | | | |
| Mechanical Characteristics | | | | | | |
| Dimensions (W*H*D) [mm] | 570*350*380 | 570*470*380 | 570*590*380 | 570*710*380 | 570*830*380 | 570*950*380 |
| Weight [kg] | 67.1 | 99.5 | 131.9 | 164.3 | 196.7 | 229.1 |
| Certificates | | | | | | |
| Safety | IEC 62619 | | | | | |
| EMC | EN IEC 61000-6-1/2/3/4 | | | | | |
| Transportation | UN38.3 | | | | | |
| Ingress Protection | IP65 | | | | | |

*1, 25°C, @90% DOD, 0.5C charging/discharging.

*2, Charge derating will occur between 0°C and +15°C.

